

AMENDMENTS TO THE CLAIMS

Please note and consider the claims in the application as identified below, with currently amended claims comprising markings in the form of strikethrough for deletions and underlining for additions.

1. (currently amended) A surgical device, comprising:
 - a) an ergonomic handle having an aperture accessible by a single finger of a user, and
a finger actuator accessible through the aperture, the finger actuator being sized and
shaped to receive the finger of the user ~~configured to receive a single finger of a user;~~
 - b) an elongated tubular portion extending from the ergonomic handle and having a longitudinal axis, ~~the finger actuator being positioned substantially in line with the~~
~~longitudinal axis of the tubular portion;~~ and
 - c) a rod functionally disposed within the tubular portion along the longitudinal axis, the rod being coupled proximally to the finger actuator and configured to be coupled distally to a functional end.
2. (original) A surgical device as in claim 1, further comprising a functional end coupled to a distal end of the rod, such that bidirectional pressure applied by the single finger to the finger actuator along the longitudinal axis manipulates the functional end in a bidirectional manner in a common direction to the bidirectional pressure.
3. (original) A surgical device as in claim 2, further comprising a ratcheting mechanism to lock the finger actuator in a fixed position, thus locking the functional end in a fixed position.
4. (original) A surgical device as in claim 2, wherein the functional end is free to rotate

around the longitudinal axis.

5. (original) A surgical device as in claim 1, wherein the elongated tubular portion is detachable from the ergonomic handle.

6. (original) A surgical device as in claim 1, wherein the ergonomic handle has a shape of a pistol grip.

7. (original) A surgical device as in claim 6, wherein a portion of the pistol grip that is substantially out of line with the longitudinal axis can be manipulated into a position that is substantially in line with the longitudinal axis.

8. (original) A surgical device as in claim 6, wherein a portion of the pistol grip that is substantially out of line with the longitudinal axis is detachable.

9. (original) A surgical device as in claim 2, wherein the functional end is selected from the group consisting of a grasper, scissors, a blade, a laser and a needle holder.

10. (original) A surgical device as in claim 2, wherein the functional end is a grasper.

11. (original) A surgical device as in claim 2, wherein the functional end is scissors.

12. (currently amended) A surgical system operated by a single finger, comprising:

- a) an ergonomic handle having an aperture accessible by a single finger of a user, and a finger actuator in the aperture, the finger actuator being sized and shaped to receive the finger of the user ~~configured to receive a single finger of a user~~;
 - b) an elongated tubular portion extending from the ergonomic handle and having a longitudinal axis, the finger actuator being positioned substantially in line with the longitudinal axis of the tubular portion; and
 - c) a rod functionally disposed within the tubular portion along the longitudinal axis, the rod being coupled proximally to the finger actuator and coupled distally to a functional end, such that bidirectional pressure applied by the single finger to the finger actuator along the longitudinal axis manipulates the functional end in a bidirectional manner in a common direction to the bidirectional pressure.
13. (original) A surgical system as in claim 12, further comprising a ratcheting mechanism to lock the finger actuator in a fixed position, thus locking the functional end in a fixed position.
14. (original) A surgical system as in claim 12, wherein the functional end is free to rotate around the longitudinal axis.
15. (original) A surgical system as in claim 12, wherein the elongated tubular portion is detachable from the ergonomic handle.
16. (original) A surgical system as in claim 12, wherein the functional end is selected

from the group consisting of a grasper, scissors, a blade, a laser and a needle holder.

17. (original) A surgical system as in claim 12, wherein the functional end is a grasper.
18. (original) A surgical system as in claim 12, wherein the functional end is scissors.
19. (currently amended) A method of manipulating a surgical instrument with a single finger, comprising the following steps:
 - a) grasping the surgical instrument with a hand of a user;
 - b) inserting the single finger of the user into a finger actuator accessible through an aperture of an ergonomic handle of the surgical instrument;
 - c) moving the single finger in a direction away from the hand, causing operation of a functional end; and
 - d) moving the single finger in a direction toward the hand, causing operation of the functional end.
20. (original) A method of manipulating a surgical instrument with a single finger as in claim 19, further comprising the step of rotating the functional end with the single finger.